



## RB 207-22/V2/ER--X-NPP

Insert bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

CSB207

UE207.SH

GAY27-XL-NPP

FHSR207

## 技术信息



### 主要尺寸和性能参数

|       |             |                            |
|-------|-------------|----------------------------|
| d     | 34.925mm    | Inside diameter            |
| D     | 72mm        | Outside diameter           |
| d1    | 登录可见尺寸, 去登录 | Outer diameter innering    |
| Dm    | 53.5mm      | Center diameter            |
| D1    | 登录可见尺寸, 去登录 | Outer ring inner diameter  |
| D2    | 登录可见尺寸, 去登录 | Seal groove diameter       |
| Be    | 19mm        | Outer ring height          |
| n     | 9.5mm       | channel distance           |
| Bi    | 34.9mm      | Inner ring height          |
| G     | 7.5mm       | Set screw hole distance    |
| (UNF) | 5/16-24     | Set screw specifications   |
| Cr    | 25800N      | Radial static load rating  |
| Cor   | 15200N      | Radial dynamic load rating |
| ≈m    | 0.4Kg       | weight                     |

\*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。您可通过我们网站上的联系表了解更多信息。

联系方式: 邮箱: [mr.suo@zrbearing.net](mailto:mr.suo@zrbearing.net)

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承