



### NA320-64/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

UEL320-64 L3

HC320-64 L3

G320-64 R3

EX320-64 L3

## 技术信息



### 主要尺寸和性能参数

d	101.6mm	Inside diameter
D	215mm	Outside diameter
d1	登录可见尺寸, 去登录	Outer diameter innering
d1	157.5mm	Center diameter
D1	登录可见尺寸, 去登录	Outer ring inner diameter
D2	登录可见尺寸, 去登录	Seal groove diameter
W	145mm	Eccentric sleeve outer diameter
Be	54mm	Outer ring height
h	16.7mm	Oil hole distance
n	39.5mm	channel distance
Bi	86mm	Inner ring height
L	109.2mm	total height
G	12mm	Set screw hole distance
Ph	31.3mm	Eccentric sleeve height
(UNF)	3/4-16	Set screw specifications
Cr	171710N	Radial static load rating
Cor	140130N	Radial dynamic load rating
≈m	13Kg	weight

联系方式: 邮箱: [mr.suo@zrbearing.net](mailto:mr.suo@zrbearing.net)

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承