



### NA319-60/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

UEL319-60 L3

HC319-60 L3

G319-60 R3

EX319-60 L3

## 技术信息



### 主要尺寸和性能参数

d	95.25mm	Inside diameter
D	200mm	Outside diameter
d1	登录可见尺寸, 去登录	Outer diameter innering
d1	147.5mm	Center diameter
D1	登录可见尺寸, 去登录	Outer ring inner diameter
D2	登录可见尺寸, 去登录	Seal groove diameter
W	140mm	Eccentric sleeve outer diameter
Be	50mm	Outer ring height
h	16.7mm	Oil hole distance
n	46.8mm	channel distance
Bi	97.3mm	Inner ring height
L	125.7mm	total height
G	14mm	Set screw hole distance
Ph	36.5mm	Eccentric sleeve height
(UNF)	3/4-16	Set screw specifications
Cr		Radial static load rating
Cor		Radial dynamic load rating
≈m		weight

联系方式: 邮箱: [mr.suo@zrbearing.net](mailto:mr.suo@zrbearing.net)

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承