



## UCT 316-50 F

Slider bearing housing unit T type, Cast iron housing, Set screw locking spherical ball bearing, T type seal

### 技术信息



### 主要尺寸和性能参数

|           |          |                                   |
|-----------|----------|-----------------------------------|
| d         | 79.375mm | Inside diameter                   |
| K         | 204mm    | Guide groove distance             |
| L         | 230mm    | Overall length                    |
| T         | 150mm    | Height of bearing seat fixed side |
| A         | 98mm     | Pocket height                     |
| n         | 34mm     | channel distance                  |
| C         | 30mm     | Guide groove width                |
| B         | 60mm     | Bearing seat width                |
| Bi        | 86mm     | Total width                       |
| H4        | 160mm    | Guide groove length               |
| H3        | 282mm    | Whole length                      |
| H2        | 42mm     | Pocket width                      |
| H1        | 30mm     | Fixed link length                 |
| H         | 174mm    | Axis distance                     |
| N         | 53mm     | Fixing holes                      |
| N1        | 102mm    | Width of bearing seat fixed side  |
| ≈m        | 15.8Kg   | weight                            |
| UC316-50F |          | Bearing Type                      |
| T316-50   |          | Bearing seat model                |
| M6*1      |          | Oil injection hole                |
| J7        |          | Assembly torque                   |
| HT200     |          | Bearing seat material             |

\*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。您可通过我们网站上的联系表了解更多信息。

联系方式: 邮箱: [mr.suo@zrbearing.net](mailto:mr.suo@zrbearing.net)

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承