



## UCT 315 F

Slider bearing housing unit T type, Cast iron housing, Set screw locking spherical ball bearing, T type seal

### 技术信息



### 主要尺寸和性能参数

|        |        |                                   |
|--------|--------|-----------------------------------|
| d      | 75mm   | Inside diameter                   |
| K      | 192mm  | Guide groove distance             |
| L      | 216mm  | Overall length                    |
| T      | 132mm  | Height of bearing seat fixed side |
| A      | 85mm   | Pocket height                     |
| n      | 32mm   | channel distance                  |
| C      | 26mm   | Guide groove width                |
| B      | 55mm   | Bearing seat width                |
| Bi     | 82mm   | Total width                       |
| H4     | 150mm  | Guide groove length               |
| H3     | 262mm  | Whole length                      |
| H2     | 36mm   | Pocket width                      |
| H1     | 27mm   | Fixed link length                 |
| H      | 160mm  | Axis distance                     |
| N      | 46mm   | Fixing holes                      |
| N1     | 90mm   | Width of bearing seat fixed side  |
| ≈m     | 12.7Kg | weight                            |
| UC315F |        | Bearing Type                      |
| T315   |        | Bearing seat model                |
| M6*1   |        | Oil injection hole                |
| J7     |        | Assembly torque                   |
| HT200  |        | Bearing seat material             |

\*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。您可通过我们网站上的联系表了解更多信息。

联系方式: 邮箱: [mr.suo@zrbearing.net](mailto:mr.suo@zrbearing.net)

电话: 0319-8509111

地址: 河北省临西县城北环路北侧-中达轴承