



NA319/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings


UEL319 L3

HC319 L3

G319 R3

EX319 L3

技术信息



主要尺寸和性能参数

| | | |
|-------|-------------|---------------------------------|
| d | 95mm | Inside diameter |
| D | 200mm | Outside diameter |
| d1 | 登录可见尺寸, 去登录 | Outer diameter innering |
| d1 | 147.5mm | Center diameter |
| D1 | 登录可见尺寸, 去登录 | Outer ring inner diameter |
| D2 | 登录可见尺寸, 去登录 | Seal groove diameter |
| W | 140mm | Eccentric sleeve outer diameter |
| Be | 50mm | Outer ring height |
| h | 16.7mm | Oil hole distance |
| n | 46.8mm | channel distance |
| Bi | 97.3mm | Inner ring height |
| L | 125.7mm | total height |
| G | 14mm | Set screw hole distance |
| Ph | 36.5mm | Eccentric sleeve height |
| (UNF) | M20*1.5 | Set screw specifications |
| Cr | | Radial static load rating |
| Cor | | Radial dynamic load rating |
| ≈m | | weight |

联系方式: 邮箱: mr.suo@zrbearing.net

电话: 0319-8509111

地址: 河北省临西县城北环路北侧-中达轴承