



UCT 205-16 F

Slider bearing housing unit T type, Cast iron housing, Set screw locking spherical ball bearing, T type seal

技术信息



主要尺寸和性能参数

| | | |
|-----------|--------|-----------------------------------|
| d | 25.4mm | Inside diameter |
| K | 76mm | Guide groove distance |
| L | 89mm | Overall length |
| T | 51mm | Height of bearing seat fixed side |
| A | 32mm | Pocket height |
| n | 14.3mm | channel distance |
| C | 12mm | Guide groove width |
| B | 24mm | Bearing seat width |
| Bi | 34.1mm | Total width |
| H4 | 51mm | Guide groove length |
| H3 | 97mm | Whole length |
| H2 | 16mm | Pocket width |
| H1 | 10mm | Fixed link length |
| H | 62mm | Axis distance |
| N | 19mm | Fixing holes |
| N1 | 32mm | Width of bearing seat fixed side |
| ≈m | 0.8Kg | weight |
| UCT05-16F | | Bearing Type |
| T205-16 | | Bearing seat model |
| M6*1 | | Oil injection hole |
| J7 | | Assembly torque |
| HT200 | | Bearing seat material |

*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。您可通过我们网站上的联系表了解更多信息。

联系方式：邮箱：mr.suo@zrbearing.net

电话：0319-5628888

地址：河北省临西县城北环路北侧-中达轴承