



NA316-51/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

UEL316-51 L3

HC316-51 L3

G316-51 R3

EX316-51 L3

技术信息



主要尺寸和性能参数

| | | |
|-------|-------------|---------------------------------|
| d | 80.96mm | Inside diameter |
| D | 170mm | Outside diameter |
| d1 | 登录可见尺寸, 去登录 | Outer diameter innering |
| d1 | 125mm | Center diameter |
| D1 | 登录可见尺寸, 去登录 | Outer ring inner diameter |
| D2 | 登录可见尺寸, 去登录 | Seal groove diameter |
| W | 119mm | Eccentric sleeve outer diameter |
| Be | 48mm | Outer ring height |
| h | 14mm | Oil hole distance |
| n | 40.5mm | channel distance |
| Bi | 81mm | Inner ring height |
| L | 106.2mm | total height |
| G | 13mm | Set screw hole distance |
| Ph | 31.8mm | Eccentric sleeve height |
| (UNF) | 5/8-18 | Set screw specifications |
| Cr | 122970N | Radial static load rating |
| Cor | 86590N | Radial dynamic load rating |
| ≈m | 6.7Kg | weight |

联系方式: 邮箱: mr.suo@zrbearing.net

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承