

Z&R®



## UC 311-32/V3/C12/G2--F

Insert bearings

UC 311 - 200 D1

### 技术信息



#### 主要尺寸和性能参数

|       |             |                            |
|-------|-------------|----------------------------|
| d     | 50mm        | Inside diameter            |
| D     | 120mm       | Outside diameter           |
| d1    | 登录可见尺寸, 去登录 | Outer diameter innering    |
| d1    | 88.5mm      | Center diameter            |
| D1    | 登录可见尺寸, 去登录 | Outer ring inner diameter  |
| D2    | 登录可见尺寸, 去登录 | Seal groove diameter       |
| Be    | 34mm        | Outer ring height          |
| h     | 10.6mm      | Oil hole distance          |
| n     | 25mm        | channel distance           |
| Bi    | 66mm        | Inner ring height          |
| k     | 2mm         | Oil hole diameter          |
| G     | 12mm        | Set screw hole distance    |
| (UNF) | 7/16-20     | Set screw specifications   |
| Cr    | 61800N      | Radial static load rating  |
| Cor   | 37800N      | Radial dynamic load rating |
| ≈m    | 1.95KG      | weight                     |

\*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。您可通过我们网站上的联系表了解更多信息。