2026-11-13 18:18:37




NA311/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

GNE55KRRB3　　UEL311 L3　　HC311 L3

G311 R3　　EX311 L3

技术信息



主要尺寸和性能参数

d	55mm	Inside diameter
D	120mm	Outside diameter
d1	登录可见尺寸，去登录	Outer diameter innering
d1	88.5mm	Center diameter
D1	登录可见尺寸，去登录	Outer ring inner diameter
D2	登录可见尺寸，去登录	Seal groove diameter
W	83mm	Eccentric sleeve outer diameter
Be	34mm	Outer ring height
h	10.6mm	Oil hole distance
n	27.8mm	channel distance
Bi	55.6mm	Inner ring height
L	73mm	total height
G	8.5mm	Set screw hole distance
Ph	22.2mm	Eccentric sleeve height
(UNF)	M10*1.25	Set screw specifications
Cr	61800N	Radial static load rating
Cor	37800N	Radial dynamic load rating
≈m	1.85Kg	weight

*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。 您可通过我们网站上的联系表了解更多信息。

联系方式：邮箱：mr.suo@zrbearing.net Tel: +86 0319 5628888 地址：河北省临西县城北环路北侧-中达轴承