



### NA308-25/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

UEL308-25 L3

HC308-25 L3

G308-25 R3

EX308-25 L3

## 技术信息



### 主要尺寸和性能参数

|       |             |                                 |
|-------|-------------|---------------------------------|
| d     | 39.69mm     | Inside diameter                 |
| D     | 90mm        | Outside diameter                |
| d1    | 登录可见尺寸, 去登录 | Outer diameter innering         |
| d1    | 65.5mm      | Center diameter                 |
| D1    | 登录可见尺寸, 去登录 | Outer ring inner diameter       |
| D2    | 登录可见尺寸, 去登录 | Seal groove diameter            |
| W     | 63.5mm      | Eccentric sleeve outer diameter |
| Be    | 28mm        | Outer ring height               |
| h     | 7.8mm       | Oil hole distance               |
| n     | 19.8mm      | channel distance                |
| Bi    | 41.3mm      | Inner ring height               |
| L     | 56.9mm      | total height                    |
| G     | 8mm         | Set screw hole distance         |
| Ph    | 20.6mm      | Eccentric sleeve height         |
| (UNF) | 3/8-24      | Set screw specifications        |
| Cr    | 33500N      | Radial static load rating       |
| Cor   | 19200N      | Radial dynamic load rating      |
| ≈m    | 0.8Kg       | weight                          |

联系方式: 邮箱: [mr.suo@zrbearing.net](mailto:mr.suo@zrbearing.net)

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承