



### NA308-24/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings


UEL308-24 L3

HC308-24 L3

G308-24 R3

EX308-24 L3

## 技术信息



### 主要尺寸和性能参数

d	38.1mm	Inside diameter
D	90mm	Outside diameter
d1	登录可见尺寸, 去登录	Outer diameter innering
d1	65.5mm	Center diameter
D1	登录可见尺寸, 去登录	Outer ring inner diameter
D2	登录可见尺寸, 去登录	Seal groove diameter
W	63.5mm	Eccentric sleeve outer diameter
Be	28mm	Outer ring height
h	7.8mm	Oil hole distance
n	19.8mm	channel distance
Bi	41.3mm	Inner ring height
L	56.9mm	total height
G	8mm	Set screw hole distance
Ph	20.6mm	Eccentric sleeve height
(UNF)	3/8-24	Set screw specifications
Cr	33500N	Radial static load rating
Cor	19200N	Radial dynamic load rating
≈m	0.8Kg	weight

联系方式: 邮箱: [mr.suo@zrbearing.net](mailto:mr.suo@zrbearing.net)

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承