2026-01-10 13:43:24

NA307-20/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

UEL307-20 L3 HC307-20 L3 G307-20 R3

EX307-20 L3

技术信息



主要尺寸和性能参数

d	31.75mm	Inside diameter
D	80mm	Outside diameter
d1	登录可见尺寸，去登录	Outer diameter innering
d1	58.5mm	Center diameter
D1	登录可见尺寸，去登录	Outer ring inner diameter
D2	登录可见尺寸，去登录	Seal groove diameter
W	55mm	Eccentric sleeve outer diameter
Be	25mm	Outer ring height
h	7.2mm	Oil hole distance
n	18.3mm	channel distance
Bi	38.1mm	Inner ring height
L	51.4mm	total height
G	6.5mm	Set screw hole distance
Ph	17.5mm	Eccentric sleeve height
(UNF)	5/16-24	Set screw specifications
Cr	27100N	Radial static load rating
Cor	15200N	Radial dynamic load rating
≈m	0.65Kg	weight

*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。 您可通过我们网站上的联系表了解更多信息。