



### NA306/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

GNE30KRRB3

UEL306 L3

HC306 L3

G306 R3

EX306 L3

## 技术信息



### 主要尺寸和性能参数

d	30mm	Inside diameter
D	72mm	Outside diameter
d1	登录可见尺寸, 去登录	Outer diameter innering
d1	52mm	Center diameter
D1	登录可见尺寸, 去登录	Outer ring inner diameter
D2	登录可见尺寸, 去登录	Seal groove diameter
W	50mm	Eccentric sleeve outer diameter
Be	24mm	Outer ring height
h	6.2mm	Oil hole distance
n	17.5mm	channel distance
Bi	36.5mm	Inner ring height
L	49.8mm	total height
G	6.5mm	Set screw hole distance
Ph	17.5mm	Eccentric sleeve height
(UNF)	M8*1	Set screw specifications
Cr	22400N	Radial static load rating
Cor	17400N	Radial dynamic load rating
≈m	0.45Kg	weight

联系方式: 邮箱: [mr.suo@zrbearing.net](mailto:mr.suo@zrbearing.net)

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承