




NA214-600/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

G214-600 R3

技术信息



主要尺寸和性能参数

| | | |
|-------|-------------|---------------------------------|
| d | 60mm | Inside diameter |
| D | 125mm | Outside diameter |
| d1 | 登录可见尺寸, 去登录 | Outer diameter innering |
| d1 | 97.5mm | Center diameter |
| D1 | 登录可见尺寸, 去登录 | Outer ring inner diameter |
| D2 | 登录可见尺寸, 去登录 | Seal groove diameter |
| W | 97mm | Eccentric sleeve outer diameter |
| Be | 30mm | Outer ring height |
| h | 9mm | Oil hole distance |
| n | 34.1mm | channel distance |
| Bi | 68.2mm | Inner ring height |
| L | 85.5mm | total height |
| G | 8.5mm | Set screw hole distance |
| Ph | 23.9mm | Eccentric sleeve height |
| (UNF) | 3/8-24 | Set screw specifications |
| Cr | 62300N | Radial static load rating |
| Cor | 45000N | Radial dynamic load rating |
| ≈m | 2.65Kg | weight |

联系方式: 邮箱: mr.suo@zrbearing.net

电话: 0319-8509111

地址: 河北省临西县城北环路北侧-中达轴承