



NA212-39/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

G1207 KRRB3

UEL212-39 L3


HC212-39 L3

YEL212-207

G212-39 R3

EX212-39 L3

技术信息



主要尺寸和性能参数

d	61.9125mm	Inside diameter
D	110mm	Outside diameter
d1	登录可见尺寸, 去登录	Outer diameter innering
d1	85mm	Center diameter
D1	登录可见尺寸, 去登录	Outer ring inner diameter
D2	登录可见尺寸, 去登录	Seal groove diameter
W	84.2mm	Eccentric sleeve outer diameter
Be	27mm	Outer ring height
h	8.2mm	Oil hole distance
n	30.9mm	channel distance
Bi	61.8mm	Inner ring height
L	77.5mm	total height
G	8mm	Set screw hole distance
Ph	22.3mm	Eccentric sleeve height
(UNF)	3/8-24	Set screw specifications
Cr	52500N	Radial static load rating
Cor	32900N	Radial dynamic load rating
≈m	1.9Kg	weight

联系方式: 邮箱: mr.suo@zrbearing.net

电话: 0319-8509111

地址: 河北省临西县城北环路北侧-中达轴承