



### NA211-35/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

G1203 KRRB3

UEL211-35 L3

HC211-35 L3

YEL211-203

G211-35 R3

EX211-35 L3

## 技术信息



### 主要尺寸和性能参数

d	55.5625mm	Inside diameter
D	100mm	Outside diameter
d1	登录可见尺寸, 去登录	Outer diameter innering
d1	77.5mm	Center diameter
D1	登录可见尺寸, 去登录	Outer ring inner diameter
D2	登录可见尺寸, 去登录	Seal groove diameter
W	76.2mm	Eccentric sleeve outer diameter
Be	25mm	Outer ring height
h	7.2mm	Oil hole distance
n	27.7mm	channel distance
Bi	55.4mm	Inner ring height
L	71.1mm	total height
G	8mm	Set screw hole distance
Ph	20.7mm	Eccentric sleeve height
(UNF)	3/8-24	Set screw specifications
Cr	43100N	Radial static load rating
Cor	29200N	Radial dynamic load rating
≈m	1.45Kg	weight

联系方式: 邮箱: [mr.suo@zrbearing.net](mailto:mr.suo@zrbearing.net)

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承