



NA209/V3/ER--RB3

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

GE45 KRRB3

UEL209 L3

HC2098 L3

YEL209

G209 R3

EX2098 L3

技术信息



主要尺寸和性能参数

| | | |
|-------|-------------|---------------------------------|
| d | 45mm | Inside diameter |
| D | 85mm | Outside diameter |
| d1 | 登录可见尺寸, 去登录 | Outer diameter innering |
| d1 | 66mm | Center diameter |
| D1 | 登录可见尺寸, 去登录 | Outer ring inner diameter |
| D2 | 登录可见尺寸, 去登录 | Seal groove diameter |
| W | 63.5mm | Eccentric sleeve outer diameter |
| Be | 22mm | Outer ring height |
| h | 6.5mm | Oil hole distance |
| n | 21.4mm | channel distance |
| Bi | 42.8mm | Inner ring height |
| L | 56.1mm | total height |
| G | 6.5mm | Set screw hole distance |
| Ph | 18.3mm | Eccentric sleeve height |
| (UNF) | M8*1 | Set screw specifications |
| Cr | 32800N | Radial static load rating |
| Cor | 20800N | Radial dynamic load rating |
| ≈m | 0.9Kg | weight |

联系方式: 邮箱: mr.suo@zrbearing.net

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承