



SA 208/V4/ER--X-NPP

Insert spherical bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

| | | |
|-----------------|---------------|-----------|
| GRAE40-XL-NPP-B | SA 208 | EN 208 S |
| YET 208 | 1240 - 40 ECG | UY 208 2S |
| ES 208 G2 | FH208-40G | |

技术信息



主要尺寸和性能参数

| | | |
|-------|-------------|---------------------------------|
| d | 40mm | Inside diameter |
| D | 80mm | Outside diameter |
| d1 | 登录可见尺寸, 去登录 | Outer diameter innering |
| Dm | 60mm | Center diameter |
| D1 | 登录可见尺寸, 去登录 | Outer ring inner diameter |
| D2 | 登录可见尺寸, 去登录 | Seal groove diameter |
| W | 60.3mm | Eccentric sleeve outer diameter |
| Be | 18mm | Outer ring height |
| h | 6.4mm | Oil hole distance |
| k | 1.9mm | Oil hole diameter |
| n | 11mm | channel distance |
| Bi | 30.2mm | Inner ring height |
| L | 43.5mm | total height |
| G | 6.5mm | Set screw hole distance |
| Ph | 18.3mm | Eccentric sleeve height |
| (UNF) | M8*1 | Set screw specifications |
| Cr | 29320N | Radial static load rating |
| Cor | 18240N | Radial dynamic load rating |
| ≈m | 0.67KG | weight |

联系方式: 邮箱: mr.suo@zrbearing.net

电话: 0319-5628888

地址: 河北省临西县城北环路北侧-中达轴承