



## RA 207/V2/ER--X-NPP

Insert bearings, eccentric sleeve locked outer spherical bearings, three-layer sealed outer spherical bearings

CSA207

UY207.SH

RAE27-XL-NPP

FHR207

## 技术信息



### 主要尺寸和性能参数

|       |             |                                 |
|-------|-------------|---------------------------------|
| d     | 35mm        | Inside diameter                 |
| D     | 72mm        | Outside diameter                |
| d1    | 登录可见尺寸, 去登录 | Outer diameter innering         |
| Dm    | 53.5mm      | Center diameter                 |
| D1    | 登录可见尺寸, 去登录 | Outer ring inner diameter       |
| D2    | 登录可见尺寸, 去登录 | Seal groove diameter            |
| W     | 55.6mm      | Eccentric sleeve outer diameter |
| Be    | 19mm        | Outer ring height               |
| n     | 9.5mm       | channel distance                |
| Bi    | 25.4mm      | Inner ring height               |
| L     | 38.7mm      | total height                    |
| G     | 6.5mm       | Set screw hole distance         |
| Ph    | 17.5mm      | Eccentric sleeve height         |
| (UNF) | M8*1        | Set screw specifications        |
| Cr    | 25800N      | Radial static load rating       |
| Cor   | 15200N      | Radial dynamic load rating      |
| ≈m    | 0.55Kg      | weight                          |

\*数据表仅为所选产品的尺寸和基本额定载荷概览。请始终遵守本产品的所有更多信息和指南。您可通过我们网站上的联系表了解更多信息。